



Product Number: 67512

Order Abbreviation: LU70/ECO

General Description: 70W
LUMALUX
ECOLOGIC
high
pressure
sodium HID
lamp, pass
Federal
TCLP test,
E39 based,
ET23.5
bulb,
universal
burn, clear,
1900K

Product Information	
Abbrev. With Packaging Info.	LU70ECO 20/CS 1/SKU
ANSI Code	S62
Approx. Lumens (initial - horizontal)	6300
Approx. Lumens (initial - vertical)	5500
Approx. Lumens (initial - vertical) 2	5580
Approx. Lumens (mean - horizontal)	5500
Approx. Lumens (mean - horizontal) 2	5580
Approx. Lumens (mean - vertical)	5500
Arc Length (in)	1.09
Arc Length (mm)	27.6
Average Rated Life - Horizontal (hr)	30000
Average Rated Life - (hr)	30000
Average Rated Life - Horizontal 2 (hr)	24000
Average Rated Life - Vertical (hr)	30000
Average Rated Life - Vertical 2 (hr)	24000
Avg Rated Life (hrs)	24000+
Base	E39 Mogul
Bulb	ET23.5

Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	1900
Diameter (in)	2.937
Diameter (mm)	74.60
Family Brand Name	Lumalux® ECO
Fixture Requirement	O
Hot Restrike Time (min)	1 MIN
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	7.75
Maximum Overall Length - MOL (mm)	197
Nominal Voltage (V)	52.00
Nominal Wattage (W)	70.00
Operating Position	Universal
Warm-up Time (min)	3-4 MINUTES